

# Superior Quality Non-substitutable



## SP-728A Features:

- 1.Suit for under 180 mm normal insole, soft insole lasting of shoe lasts.
- 2.Position of rising height of shoe lasts adopts high-low-speed oil system which can control accurately to achieve the betterlasting result.
- 3. Wipers and positioning pole could choose to back-mode to adjust the heel upper after fastening the last. (Patent has been applied) (fig. 1.2.3)
- 4.Lasting movement of wipers could be adjusted outside and equipped the numeral displayer, more convenient for different shoe lasts adjustment.(fig.4)
- 5. The fastener, supporter rising and inside-pull pressures are adjusted outside and equipped the pressure list, easy to operate. (Patent has been applied) (fig. 5)
- 6. We provide any kind of wipers and fasteners, fit for every shoes, the fastener is covered by chains to achieve the best result.
- 7. The last supporter has two press steps with the wiper hitting equipment to make the lasting smoothly without any angle to achieve the best result.
- 8. Also fit for Good Year lasting, we provide the stitch down shoes spare parts to use.

## SP-727A Features:

- 1. This machine is suitable for lasting the shoes with general and soft midsoles and with the heels at the height less than 180mm.
- 2.Positioning rod is equipped the height micro-adjustment structure, which makes the height of shoe lasting adjustment easily and accurately to position.
- 3. We have full sizes of wipers and toe forming bands which were wrapped by chain to fit any shape of shoes for the best result.
- 4. Auxiliary supporter adopts gears, gear racks and ratchets, quick and accurate to adjust the height.
- 5. The second time pressing of last supporter is designed to work with the wiper pre-heat device to keep heel smoothly and no angles, increasing the lasting result to upgrade the shoe quality. It makes the lasting areas smoothly, increases the lasting result, and upgrades the quality of shoes.
- 6. The stitching down construction equipment is optional for producing the stitching down shoes.





束緊器、撐台上升、撐台內拉等壓力, 其壓力可顯示與調整

Pressures of fastener, supporter rising, inside-pull could be displayed and adjusted



### SP-727A

油壓自動後幫機 Hydraulic Automatic Heel Lasting Machine

	型 號 Model	728A	SP-727A
馬力	Power	1.5KW / 2 HP	1.5KW / 2 HP
電熱	Heating Power	0.8 kw	0.8 kw
使用壓力	Hydraulic Pressure	40 kg/cm <sup>2</sup>	40 kg/cm <sup>2</sup>
產里	Productivity	3000 pairs/8 hour	3000 pairs/8 hour
净 重	N.W.	430 kg	432 kg
毛重	G.W.	出貨時提供/Be provided before shipment	
機械尺寸	Dimension(L X W X H)	750(L)×1150(W)×1450(H)mm	$750(L) \times 970(W) \times 1450(H) mm$
包装尺寸	Packing Size(L×W×H)	780(L)×1260(W)×1700(H)mm	$780(L) \times 1250(W) \times 1700(H)$ mm
液壓油量	Hydraulic Oil Capacity	50 liters	50 liters

#### 本公司保有隨時變更設計之權利,不另通知。

We reserve the rights to change the descriptions and features, without notice.



# 台灣工廠 Taiwan Factory:

# 就鋒興業股份有限公司 SINCERE PIONEER ENTERPRISE CO., LTD.



42846台灣台中市大雅區前村路128號 No.128, Ciancun Rd., Daya Dist., Taichung City 42846, Taiwan. TEL:+886-4-25653836(Rep) FAX:+886-4-25653236

FAX:+886-4-25653236 Web:www.dgspm.com E-mail:sptw-sales@dgspm.com.tw

# 中國工廠 China Factory:

## 東莞市誠鋒機械有限公司 SINCERE PIONEER MACHINERY CO., LTD.

廣東省東莞市厚街鎮橋頭村第三工業區 3 rd Industrial Zone,QiaoTou,Houjie Town, DongGuan,GuanDong Province,China. 電話:+86-769-855087777(Rep.) 傳真:+86-769-85585860 免費客户投訴專綫:800-900-9869 Web://www.dgspm.com E-mail:sp@dgspm.com